



Order Form: Slimline Lift Chair

Prepared by _____
Client Name _____
Order Date _____
Reference No. _____

Circle required dimensions and configurations

CONFIGURATION

Mechanism	Single Motor Zero-G Mech with adjustable headrest & lumbar				Dual Motor Zero-G Mech with adjustable headrest & lumbar			
Size	MINI		A		B			
Wheels	Integrated Retractable Wheels (Standard)				Remove Wheels			
Memory Foam	Seat		Legrest		Backrest		Armrest	
Cushion Insert	None (Standard)	16x16 Low Profile	16x16 High Profile	18x16 Low Profile	18x16 High Profile	20x16 Low Profile	20x16 High Profile	
Controller Option	Right (Standard)				Left			
Other Options	24V Rechargeable Battery Pack				Scotch Guard			
					Include Infill Plug			

DIMENSIONS

	Seat Depth (mm)	Seat Height (mm)	Seat Foam (mm)	Seat Width (mm)	Arm Height (mm)	Back Height (mm)	Footrest Length (mm)
Mini Modifications	-25						-50
Mini Standard Size	455	445	80	500	165	655	230
Mini Modifications	+25	+30		+50	+30	+30	
	+50					+60	
A Modifications	-50	-30				-30	-50
A Standard Size	495	475	110	500	165	675	230
A Modifications	+25	+30		+50	+30	+30	
B Modifications	-50	-30				-30	-50
B Standard Size	535	490	130	500	165	695	230
B Modifications				+50	+30	+30	

NOTE: *Reduced seat foam limits Safe working load to 90kg and reduces seat foam warranty to 2 years.

*All cushion insert modifications must be produced as a removable seat

*Low profile cushions only for the Mini size

**+50mm seat width modification required to use 20x18 insert

COLOUR AND FINISH

Fabric Inner _____
Outer _____

ADDITIONAL NOTES

